



## Polyfluo<sup>®</sup> 400

A high performance wax/PTFE combination for improved surface lubricity with scratch resistance

### Features and Benefits

- High performance product for adding slip and abrasion resistance
- Synergistic wax combination that enhances PTFE mobility to the coating surface
- High slip wax provides excellent surface lubricity
- PTFE dramatically enhances abrasion resistance
- Conforms to (EU) 2019/1021 & Stockholm Convention (POP)

### Composition

Wax modified PTFE

### Recommended Addition Levels

0.5-3.0% (on total formula weight)

### Systems and Applications

Water based, solvent based and energy curable coatings and inks. Industrial coatings (including plastic and metal); wood coatings; printing inks and OPV's (including flexo and gravure); powder coatings; interior and exterior can and container coatings; coil coatings; rubber additives.

### Typical Properties\*

	<u>Polyfluo 400</u>	<u>Polyfluo 400XF</u>
Melting Point °C	108 - 115	108 - 115
Density @ 25 °C (g/cc)	1.21	1.21
NPIRI Grind	1.0 - 2.0	1.0 - 1.5
Maximum Particle Size (µm)	22.00	11.00
Mean Particle Size (µm)	5.0 - 6.0	3.0 - 5.0

This product is also available as a water based wax dispersion - Microspersion PF400-50

Mar-23